



HALOGEN
VALVE SYSTEMS, INC.

Your Partner in Safety

Emergency Chlorine Cylinder Valve Shutoff System

TERMINATOR™ CHLORINE VALVE ACTUATOR

Bulletin: 702



Features

- Economical, low cost solution
- Protects personnel and community by quickly and automatically stopping a gas leak
- Easy-to-use gravity mount design for 150 lb (68 kg) cylinders
- Battery powered system – continues to protect for up to 5 days if AC power lost
- Fire code approved for many applications as scrubber alternative
- Helps comply with RMP gas leak mitigation requirement
- Compatible with all cylinder mounted vacuum regulators
- Actuator retention pin for added security

The Terminator valve actuator with Gemini controller is an economical emergency chlorine shutoff system designed for use on 150 lb (68 kg) type chlorine and sulfur dioxide cylinders commonly used at water and wastewater treatment plants. The system is DC electric powered with AC only used for keeping battery optimally charged at all times. In the event of a loss of AC power, the system continues to protect for 3 to 5 days. If AC power remains off for an extended period of time, the system will auto-initiate emergency close while sufficient battery power remains.

The Terminator is compatible with standard valves meeting Chlorine Institute specifications and requires no tools or adapters for installation. The Terminator is simply placed on the cylinder valve after process connections are made, leak tested, and the valve opened. Being a safety device, the Terminator is only powered in the closing direction.

When the Gemini controller receives an emergency close signal from a gas detector, emergency shutoff switch, or other input, the Terminator is activated and the cylinder valve is rapidly closed. One or two Terminator actuators may be controlled by the Gemini, making this the perfect safety solution for both single and dual cylinder applications. System includes a low voltage 24VDC relay output for remote indication of emergency close activation and an optional relay interface module provides dry contact relays with latching capabilities when required.

Halogen Valve Systems, Inc.

17961 Sky Park Circle,
Suite A
Irvine, CA 92614 USA

Tel: +1 949-261-5030
Fax: +1 949-261-5033
Toll Free (877) 476-4222

www.halogenvalve.com



Your Partner in Safety

Emergency Chlorine Cylinder Valve Shutoff System

TERMINATOR™ CHLORINE VALVE ACTUATOR

Bulletin: 702

Specifications

Enclosure:	XENOY™, NEMA 4X
Drive Shaft:	440C Stainless Steel
Drive Bushing:	XYLAN® Aluminum-Silicon Bronze
Cable:	7 ft (2.14m), 2 Wire
Closing Torque:	40 ft-lb
Charging Current @110/220 VAC:	0.9A MAX
Charging Current @12VDC (Solar):	0.34A MAX
Battery Type:	12VDC, 8.0 Amp-Hour, High Rate
Standby/Backup Time:	Up to 5 days
Standard Compatibility:	Chlorine Institute DWG's 110, 113
Yoke Compatibility:	Chlorine Institute DWG's 189, 131

Terminator actuators require the Gemini controller for a complete emergency valve shutoff system. Actuators cannot operate stand alone.



Model Information

Image	Model	Description
	8001.14	Gemini Controller with: (1) Terminator Actuator, (1) Storage Bracket, (1) Emergency Shutoff Switch
	8002.14	Gemini Controller with: (2) Terminator Actuators, (2) Storage Brackets, (1) Emergency Shutoff Switch

Options/Accessories

Part No.	Description
4500.05	Relay Interface Module—5A, 250VAC Dry Contact
4500.06-A	Manual Relay Reset Button (requires Relay Interface Module, P/N 4500.05)
5151.00	Open Style Yoke
6888.00	Yoke to Pigtail Adapter
2202.00	Auxiliary Valve Adapter
6430.00	Additional Emergency Close Switch
8600.00	Additional Actuator Storage Bracket